
## TerraPave Porous Pavers

## SPECIFICATION SHEET

Interlocking Cellular Paving System



**TerraPave Porous Pavers** are an interlocking cellular paving system for ground reinforcement. The grids can be installed with either a grass or gravel filled surface and provide a durable, environmentally friendly reinforced surface able to cope with extremely heavy loads.

PUBLICATION DETAILS	
ISSUE NUMBER	O2
DATE	JUNE 2025

## SPECIFICATIONS

TECHNICAL SPECIFICATIONS	
MATERIAL	Recycled HDPE
DIMENSIONS	500 x 500 x 40mm
COLOUR Black	Black
HEIGHT	4Omm
CELL'S DIAMETER	6Omm
WEIGHT	O.9kg ± 7 %
MAXIMUM LOAD BEARING CAPACITY	16OT/m2 - 2OOT/m2 (filled and compacted)
REQUIRED QTY/M2	4 pcs
THICKNESS OF INNER WALL	5mm
LOAD CLASS /DIN EN 1072	16/16 T
LOAD CLASS /DIN EN 1072 TEMPERATURE RANGE	16/16 T -10°C to 50°C
	10.10
TEMPERATURE RANGE	-10°C to 50°C
TEMPERATURE RANGE ESTIMATED LIFE SPAN	-10°C to 50°C  20 years  Applicable to: road salt, ammonia, alcohol, oil, gasoline,

DISCLAIMER The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented here is intended only as a general guide to the use of such products and no liability is accepted by Advance Landscape Systems Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information.

